

Chiller ANL 110 WRK 111L-2-E-PT

Cooling capacity [kW]

Outdoor temp.		20 °C	15 °C	10 °C	5 °C	0 °C	-5 °C	-10 °C
	35 °C	-	123	109	95.1	78.4	66.2	54.8
	25 °C	-	141	125	109	90.8	77.4	65

Electrical data

Supply voltage	400 V / 50 Hz / 3 Ph
Electrical connection	125 A CEE Stecker A
Current at rated load	58.1 A
Max. current draw	93 A
Power at rated load	40.2 kW
Minimum cable cross-section for 25 m feed	125 A CEE 5x35 mm ²

Refrigeration circuit

Refrigerant	R410A
Number of refrigeration circuits	2
Number of compressors	2

Consumer circuit

Internal pump	1,5 - 3,8 bar
Volume flow	8,1 - 48
Buffer tank	500 l

Dimensions and weight

Length	3.300 mm
Width	1.300 mm
Height	2.400 mm
Weight	1.831 kg

Connections

Consumer	2" Kamlock
Filling connection	1/2"

Sound pressure level

at 10 m	61.5 dB(A)
---------	------------

Operating environment

min. -20 °C bis max. 43 °C

Coolant

Wasser, Wasser / Glykol