

## Chiller ANL 114 WRK 40L-1-PT

### Cooling capacity [kW]

Outdoor temp.		20 °C	15 °C	10 °C	5 °C	0 °C	-5 °C	-10 °C
	35 °C		51.7	45.2	40.6	36	30.2	26.2
25 °C		58.9	51.6	46.3	41	34.5	29.8	25.6

#### Electrical data

Supply voltage	400 V / 50 Hz / 3 Ph
Electrical connection	63 A CEE Stecker A
Max. current draw	36 A
Power at rated load	19 kW
Minimum cable cross-section for 25 m feed	63 A CEE 5x10 mm <sup>2</sup>

#### Refrigeration circuit

Refrigerant	R410A
Number of refrigeration circuits	1
Number of compressors	1

#### Consumer circuit

Internal pump	2,8 - 1,7 bar
Volume flow	3,2 - 18
Buffer tank	255 l

#### Dimensions and weight

Length	2.250 mm
Width	950 mm
Height	1.800 mm
Weight	725 kg

#### Connections

Consumer	2" Kamlock
Filling connection	1/2"

#### Sound pressure level

at 10 m	55 dB(A)
---------	----------

#### Operating environment

min. -20 °C bis max. 43 °C

#### Coolant

Wasser, Wasser / Glykol