

## Chiller ANL 171 WRK-94,8L-PT

### Cooling capacity [kW]

Outdoor temp.		20 °C	15 °C	10 °C	5 °C	0 °C	-5 °C	-10 °C
	35 °C	-	107	94.8	82.9	68.7	58.1	48.2
25 °C	-	121	108	94.5	78.7	67.2	56.6	

#### Electrical data

Supply voltage	400 V / 50 Hz / 3 Ph
Max. current draw	168 A
Power at rated load	44 kW
Minimum cable cross-section for 25 m feed	125 A CEE 5x25 mm <sup>2</sup>

#### Refrigeration circuit

Refrigerant	R410A
Number of refrigeration circuits	2
Number of compressors	2

#### Consumer circuit

Internal pump	2,1 - 3,5 bar
Volume flow	6,6 - 36
Buffer tank	500 l

#### Dimensions and weight

Length	3.300 mm
Width	1.300 mm
Height	2.100 mm
Weight	1.224 kg

#### Connections

Consumer	3" Kamlok
Filling connection	1/2"

#### Sound pressure level

at 10 m	62 dB(A)
---------	----------

#### Operating environment

min. -5 °C bis max. -46 °C

#### Coolant

Wasser, Wasser 65% / Polar N 35%