



Chiller ANL 193 WRK 62L-1-PT

Cooling capacity [kW]

Supply temperature								
Outdoor temp.		20 °C	15 °C	10 °C	5 °C	0 °C	-5 °C	-10 °C
	35 °C	85	74.9	62.3	54.6	45.4	38.7	32.5
	25 °C	96	84.1	70.8	62.4	52	44.7	37.8

Electrical data

Supply voltage	400 V / 50 Hz / 3 Ph
Electrical connection	CEE 63 A
Max. current draw	54 A
Power at rated load	22 kW
Minimum cable cross-section for 25 m feed	63 A CEE 5x16 mm ²

Refrigeration circuit

Refrigerant	R410A
Number of refrigeration circuits	1
Number of compressors	2

Consumer circuit

Internal pump	3,3 - 0,9 bar
Volume flow	4,8 – 27 m ³ /h
Buffer tank	350 l

Dimensions and weight

Length	2.300 mm
Width	900 mm
Height	2.100 mm
Weight	1.099 kg

Connections

Consumer	2" Kamlok
Filling connection	1/2"

Sound pressure level

at 10 m	58 dB(A)
---------	----------

Operating environment

min. -20 °C max. 43 °C

Coolant

Wasser, Wasser/ Glykol
